TITLE OF THE INVENTION

DIELECTRIC FILTER

FIELD OF THE INVENTION

5   The present invention relates to dielectric filters to

be incorporated into mobile communications devices for

determining the frequency band pass characteristics of

signals to be processed.

BACKGROUND OF THE INVENTION

10   With mobile communications devices such as portable

telephones adapted to have a multiplicity of functions in

recent years, it is required that these devices be usable for

a multiplicity of bands and have satisfactory frequency

characteristics in wide frequency bands. It is known that

15   dielectric filters are used in such mobile communications

devices for transmitting and receiving signals, for example,

in a frequency band of hundreds of megahertz to several

gigahertz. FIG. 7 shows the construction of a dielectric

filter for use in conventional mobile communications devices

20   (see JP-B No. 7-254806).

         With reference to FIG. 7, a dielectric block 1 in the

form of a rectangular parallelepiped and made from a

dielectric material such as a ceramic material has two

through bores 2, 4 extending through the block from the front

end face 14 thereof to the rear end face 12 thereof. The

through bores 2, 4 comprise large-diameter bore portions 21,

41 and small-diameter bore portions 22, 42, respectively. An

outer conductor 5 comprising a conductor layer of silver or

5   the like is formed over the outer peripheral surface (upper

and lower surfaces and opposite side surfaces) of the

dielectric block 1. An inner conductor 3 is formed over each

of the inner peripheral surfaces of the block defining the

through bores 2, 4. A conductor layer is formed also on the

10   rear end face 12 of the block 1 to provide a short-circuiting

end face for short-circuiting the outer conductor 5 and the

inner conductor 3. The dielectric block 1 is left exposed

over the front end face 14 thereof to provide an open end

face to leave the through bore 2 and the inner conductor 3

15   open.

A pair of input and output electrodes 6, 6 each

comprising a conductor layer are formed on the outer

peripheral surface of the block 1. Electrode separating

regions 8, 8 are formed between the outer conductor 5 and the

20   input and output electrodes 6, 6 by cutting out the conductor

layer. A bridge portion 51 comprising a part of the outer

conductor 5 is formed between the input and output electrodes

6, 6.

FIG. 9 is an equivalent circuit diagram of the

conventional dielectric filter described. A pair of
resonators A, A are coupled to the input and output
electrodes 6, 6, respectively, each via a capacitance C1, and
the two resonators A, A are coupled to each other by a

5   magnetic field M.

FIG. 8 shows the frequency characteristics of the
conventional dielectric filter described. There is an
attenuation pole c1 at the high frequency side of a pass band
a1, and there is an attenuation pole b1 at the low frequency

10   side thereof, whereby a band pass filter is realized.

With the dielectric filter shown in FIG. 7, a resonance
frequency is set in the desired pass band a1 by varying the
axial lengths of the small-diameter bore portions 22, 42 of
the through bores 2, 4, and the width of the pass band is

15   adjustable by varying the distances of the input and output
electrodes 6, 6 from the large-diameter bore portions 21, 41
of the through bores 2, 4 and thereby varying the degree of
the capacitance coupling.

With the conventional dielectric filter shown in FIG. 7,

20   the position (frequency) of the attenuation pole b1 at the
low frequency side is adjustable to some extent by altering
the external dimensions of the dielectric block and the
arrangement of the large-diameter bore portions and the
small-diameter bore portions of the through bores, whereas

difficulty is encountered in making a similar adjustment of the attenuation pole c_1 at the high frequency side. Moreover, the fabrication of the filter involves the problem that it is very cumbersome to alter the shape of the through bores of the dielectric block.

Although the attenuation characteristics in a high frequency band outside the pass band also become important because communications devices in recent years are adapted to have a multiplicity of functions, conventional dielectric filters have the problem of being unable to fully attenuate a higher harmonic e_1 produced in a high frequency band (around 5 GHz) corresponding to about 3 times the pass band a_1 as shown in FIG. 8 and being seriously impaired in filter characteristics.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a dielectric filter having frequency characteristics in the pass band which are improved by increasing the number of attenuation poles, the filter being adapted to fully suppress a higher harmonic produced in a high frequency band.

The present invention provides a dielectric filter which comprises a dielectric block in the form of a rectangular parallelepiped and having a plurality of through bores extending therethrough in parallel to each other, an outer

conductor in the form of a conductor layer and covering an outer peripheral surface of the block in parallel to the extending direction of the through bores and one end face of the block wherein one end of each of the through bores has an

5   opening, an inner conductor in the form of a conductor layer and covering an inner periphery of the block defining each of the through bores, and a pair of input and output electrodes formed on the surface of the block and separated from the outer conductor. The other end face of the block wherein the

10   other ends of the through bores have openings is in the form of an open end face having no conductor layer. The pair of input and output electrodes are opposed to each other on one plane providing the outer peripheral surface of the block, and a dielectric block exposing portion having no conductor

15   layer thereon is formed between the two electrodes. The block is provided in the other end face thereof with at least one groove dividing the open end face, and the groove is provided with a conductor in conduction with the outer conductor.

20   With the dielectric filter of the present invention, the pair of input and output electrodes are directly opposed to each other to thereby provide second capacitance coupling between the two electrodes, whereby an additional attenuation pole is formed anew. The frequency characteristics in the

pass band are therefore improved by a larger number of

attenuation poles than is conventionally available. The

structure wherein the open end face is divided by the groove

provides a fortified ground for the filter, with the result

5   that a higher harmonic having three times the frequency of

the pass band can be fully suppressed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing an embodiment of

dielectric filter according to the invention;

10   FIG. 2 is a diagram showing the frequency

characteristics of the dielectric filter;

FIG. 3 is an equivalent circuit diagram of the

dielectric filter;

FIG. 4 is a graph showing the relationship between the

15   depth of a groove and the frequency of an attenuation pole;

FIG. 5 is a graph showing the relationship between the

groove width and the frequency of the attenuation pole;

FIG. 6 is a graph showing the relationship between the

distance between input and output electrodes and the

20   frequency of attenuation poles;

FIG. 7 is a perspective view showing a conventional

dielectric filter;

FIG. 8 is a diagram showing the frequency

characteristics of the dielectric filter;

FIG. 9 is an equivalent circuit diagram of the dielectric filter.

DETAILED DESCRIPTION OF EMBODIMENT

An embodiment of the invention will be described below
5   in detail with reference to the drawings. FIG. 1 shows a
dielectric filter embodying the invention and comprising a
dielectric block 1 in the form of a rectangular
parallelepiped and made, for example, from a ceramic material
of the $BaTiO_3$ type. The dielectric block 1 has two through
10 bores 2, 4 extending through the block from the front end
face 11 thereof to the rear end face 12 thereof. Each of the
through bores 2, 4 comprises a large-diameter bore portion 21,
41 and a small-diameter bore portion 22, 42 extending from
the bore portion 21, 41 and coaxial therewith.

15   An outer conductor 5 comprising a conductor layer of
silver or the like is formed over the outer peripheral
surface (upper and lower surfaces and opposite side surfaces)
of the dielectric block 1. An inner conductor 3 is formed
over each of the inner peripheral surfaces of the block
20 defining the through bores 2, 4. A conductor layer is formed
also on the rear end face 12 of the block 1 to provide a
short-circuiting end face for short-circuiting the outer
conductor 5 and the inner conductor 3. The dielectric block
1 is left exposed over the front end face 11 thereof to

provide an open end face for leaving the through bore 2 and the inner conductor 3 electrically open.

A pair of input and output electrodes 6, 6 each comprising a conductor layer are formed on the outer

5 peripheral surface of the block 1. Electrode separating regions 8, 8 are formed between the outer conductor 5 and the input and output electrodes 6, 6 by cutting out the conductive layer. The input and output electrodes 6, 6 are opposed to each other on one plane providing the outer

10 peripheral surface of the dielectric block 1, and a dielectric block exposing portion 13 having no conductor layer is formed between the two electrodes 6, 6.

Formed in the open end face 11 of the dielectric block is a groove 7 extending between the two through bores 2, 4

15 having respective openings in the open end face 11 to divide the open end face 11 in two. The inner surface defining the groove 7 is provided with a conductor layer providing a portion of the outer conductor 5.

The dielectric filter having the above construction is

20 usable to provide a filter of two-stage structure having a pass band, for example, with a center frequency of 1575 MHz. When the pass band is determined in this case, the block size of the dielectric filter and the size of through bores thereof are determined in accordance with the material of the

block. The dielectric filter measures, for example,

approximately 3.5 mm × 3.6 mm × 1.8 mm.

FIG. 3 shows an equivalent circuit diagram of the

dielectric filter embodying the invention. A pair of

5   resonators A, A are coupled to the input and output

electrodes 6, 6, respectively, each via a first capacitance

C2, and the two resonators A, A are coupled to each other by

a magnetic field M. The two input and output electrodes 6, 6

are further connected to each other via a second capacitance

10   C3. The second capacitance C3 is provided by positioning the

pair of input and output electrodes 6, 6 as opposed to each

other without interposing any conductor layer therebetween.

FIG. 2 shows the frequency characteristics of the

dielectric filter according to the foregoing embodiment. At

15   the high frequency side of the pass band a2, there are an

attenuation pole b2 corresponding to the conventional

attenuation pole b1 and another attenuation pole c2

corresponding to the conventional attenuation pole c1, and an

attenuation pole d2 appears anew at the low frequency side

20   (around 800 MHz). Consequently, the band pass filter thus

realized has sharp attenuation characteristics. A higher

harmonic e2 having approximately three times the frequency of

the pass band is fully suppressed.

The attenuation pole b2 at the high frequency side of

the pass band corresponds to the conventional attenuation

pole b1 at the low frequency side, as shifted toward the high

frequency side of the pass band. This is attributable to a

change of the coupling relationship between the resonators

5   from the capacitive type to the inductive type due to the

provision of the groove 7 in addition to the magnetic

coupling between the resonators. Further the appearance of

the new attenuation pole d2 at the low frequency side of the

pass band is due to the second capacitance coupling C3

10   produced by the foregoing opposed relationship between the

pair of input and output electrodes.

Thus, the dielectric filter embodying the invention

realizes frequency characteristics having three attenuation

poles, so that filters can be realized which are adapted to

15   separate signals of pass bands of different standard (in the

cellular telephone system in use in the U.S., 800-MHz-band

which is AMPS band at the low frequency side of the pass band,

or 1.8-GHz-band which is DCS band or 2.4-GHz-band for use in

LAN at the high frequency side thereof), unlike the original

20   pass band (for example, of 1575 MHz), and which are

applicable to communications devices for use with a

multiplicity of bands. Stated more specifically, the

attenuation pole d2 appearing anew at the low frequency side

of the pass band can be assigned to the band of 800 MHz, and

the two attenuation poles b2 and c2 present at the high

frequency side of the pass band can be assigned to the band

of 1800 MHz, i.e., DCS band, and 2.4-GHz-band for LAN.

FIGS. 4 to 6 are graphs showing results of experiments

5   conducted to measure variations in the frequency of

attenuation pole or poles when the depth D or width W of the

groove 7 shown in FIG. 1, or the distance T between the input

and output electrodes was altered, respectively. The graphs

of FIGS. 4 and 5 indicate that the frequency of the

10 attenuation pole b2 at the high frequency side of the pass

band is adjustable by varying the depth D or width W of the

groove. The graph of FIG. 6 reveals that the frequencies of

the attenuation pole d2 at the low frequency side of the pass

band and the attenuation pole c2 at the high frequency side

15 thereof can be adjusted by varying the distance T between the

input and output electrodes. Thus, the frequencies of the

three attenuation poles can be altered to provide attenuation

poles at desired frequencies by suitably varying the above

dimensions.

20 . The conductor layer formed on the inner surface defining

the groove 7 provides a fortified ground around the through

bores 2, 4 which have openings in the open end face 11, so

that the higher harmonic e2 having three times the frequency

of the pass band can be fully suppressed. This ensures the

application of the filter also to high-frequency transmission devices for use in wireless LAN.

With the dielectric filter of the present invention described above, a pair of input and output electrodes are directly opposed to each other with no conductor layer interposed therebetween to thereby provide second capacitance coupling between the two electrodes and cause an additional attenuation pole d2 to appear anew. Furthermore, the structure wherein the open end face 11 is divided by the groove 7 provides a fortified ground for the filter to ensure satisfactory suppression of higher harmonic.

The attenuation pole d2 at the low frequency side of the pass band and the attenuation pole c2 at the high frequency side thereof are adjustable in frequency by varying the distance between the pair of input and output electrodes, while the frequency of the attenuation pole b2 at the high frequency side of the pass band can be adjusted by varying the width and depth of the groove. The attenuation poles in the vicinity of the pass band can therefore be adjusted as desired. This makes it possible to design filters adapted for use in a multiplicity of varying bands.